



YOU'RE IN CONTROL WITH OUR HYDRO-DRIVE WALK-BEHIND



MOW WITH
3 YEAR LIMITED
WARRANTY
CONFIDENCE™

DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP

THE ULTIMATE IN MOWING QUALITY, DURABILITY AND EASY OPERATION

Our Hydro-Drive Walk-Behind mowers provide productive performance and superior results with a range of options to suit your budget and mowing needs. Available with a standard or floating deck and your choice of our patented Z-Control™ or SoftGrip™ EZ controls, the Hydro-Drive models will keep you comfortable all day while delivering a killer cut.

FEATURES:

- » Heavy-duty, durable electric clutch
- » Float deck models to help prevent scalping in uneven terrain
- » No-flat front caster wheels
- » Full pump and wheel motor design
- » Kawasaki® FS engines with heavy-duty air cleaners (on float deck models)
- » A reliable belt routing system to ensure long belt life and low maintenance costs
- » Intuitive controls to make every job easier to handle
- » 5-gallon fuel tank to keep you cutting longer



| | Hydro 933305 | Hydro 934306 | Hydro Electric Start 934307 | Hydro 935308 | Z-Control Hydro 934332 | |
|------------------------|--|--|--|--|------------------------------|------------------------------|
| ENGINE | Kawasaki® FS481V | Kawasaki® FS541V | Kawasaki® FS541V | Kawasaki® FS600V | Kawasaki® FS541V | |
| Displacement | 603 cc | | 603 cc | | 603 cc | |
| Lubrication | Full pressure - Spin on filter | | Full pressure - Spin on filter | | | |
| Fuel Capacity | 5 gal. | | 5 gal. | | 5 gal. | |
| Air Filtration | Dual Element | | Dual Element | | Dual Element | |
| Mower Deck | DuraDeck™ side discharge with molded rubber chute; Fabricated 7-gauge deck top plus 7-gauge reinforcements | | DuraDeck™ side discharge with molded rubber chute; Fabricated 7-gauge deck top plus 7-gauge reinforcements | | | |
| Width | 36" | 48" | 48" | 52" | 48" | |
| Cutting Height | 1.38" – 4.63" | | 1.38" – 4.63" | 1.38" – 4.63" | 1.38" – 4.63" | |
| DECK | Blade Tip Speed | 16,964 fpm @ 3600 engine rpm | 15,315 fpm @ 3600 engine rpm | 15,315 fpm @ 3600 engine rpm | 16,964 fpm @ 3600 engine rpm | 15,315 fpm @ 3600 engine rpm |
| Deck Skirts | 7-gauge skirts | | 7-gauge skirts | 7-gauge skirts | 7-gauge skirts | |
| Spindle Type | Maintenance-free with 1" shaft | | Maintenance-free with 1" shaft | | | |
| Spindle Bearing | Double-sealed, precision ground ball bearings | | Double-sealed, precision ground ball bearings | | | |
| Deck Drive | Warner Mag Stop 125 ft. lb. electric clutch | | Warner Mag Stop 125 ft. lb. electric clutch | | | |
| SIZE | Machine Length | 78" | 78" | 78" | 78" | |
| Machine Height | 40.3" | | 40.3" | 40.3" | 40.3" | |
| Machine Weight | 528 lbs. | 582 lbs. | 582 lbs. | 593 lbs. | 528 lbs. | |
| TRANSMISSION | Type | Hydro-Gear variable displacement pumps | | Hydro-Gear variable displacement pumps | | |
| Pump Size | 10 cc pumps with separate wheel motors | | 10 cc pumps with separate wheel motors | | | |
| Ground Speed | 6 mph | | 6 mph | 6 mph | 6 mph | |
| WHEELS | Front Tires | 9 x 3.5-4 no-flats | | 9 x 3.5-4 no-flats | 9 x 3.5-4 no-flats | |
| Rear Tires | 16 x 7.5-8 4-ply | | 16 x 7.5-8 4-ply | 16 x 7.5-8 4-ply | | |
| Drum | Hydrostatic dynamic braking - parking brake | | Hydrostatic dynamic braking - parking brake | | | |
| WARRANTY | 3-year / 2500 hour Best in Industry MOW WITH CONFIDENCE™ Limited Warranty | | | | | |

DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP

HUNT DOWN YOUR NEAREST BOB-CAT® DEALER AT BOBCATTURF.COM | 866-469-1242

