



# THE CAT'S OUT OF THE BOX

Introducing the  
**QuickCat™**

**THE NEW STANDARD IN STAND-ON MOWERS**

**DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP**

# THIS CAT'S GOT CLAWS!

The ultimate in stand-on mower durability, quality of cut and ease of ownership

Built on over 40 years of engineering and manufacturing excellence to be the best performing, most reliable and toughest stand-on mower ever, the nimble BOB-CAT® QuickCat™ makes quick work of the most challenging commercial turf jobs small or large-acreage estates. Its ground speed, confidence-inspiring stability and all-day comfort make the QuickCat™ the new standard in stand-on mowers.

## THE QUICKCAT™ FEATURES:

- » Up to 8 mph mowing speed and 10.5 mph transport speed
- » Optimal operator station placement for excellent center of mass stability
- » Extra-large drive tires for a smoother ride and better traction
- » Low placement of the fuel tank for improved balance on uneven ground
- » Large fuel tank for all-day mowing without refueling
- » Compact size for maneuvering in tight spaces and loading on crowded trailers
- » True floating deck improves cut quality and maintenance
- » Extra ground clearance to safely move on and off high curbs
- » Extra-strong DuraDeck™ mower deck, backed by a limited lifetime warranty



		QuickCat™ 912360	QuickCat™ 912480	QuickCat™ 912520	QuickCat™ 912610
<b>ENGINE</b>	<b>Model</b>	Kawasaki FX600V	Kawasaki FX651V	Kawasaki FX691V	Kawasaki FX730V
	<b>Displacement</b>	603 cc	726 cc	726 cc	726 cc
	<b>Fuel Capacity</b>	5.1 gal.	6.5 gal.	6.5 gal.	6.5 gal.
	<b>Air Filtration</b>	Dual Stage Canister	Dual Stage Canister	Dual Stage Canister	Dual Stage Canister
<b>ELECTRICAL</b>	<b>Charging System</b>	15 amp	15 amp	15 amp	15 amp
	<b>Clutch</b>	125 ft. lb.	200 ft. lb.	200 ft. lb.	200 ft. lb.
<b>DECK</b>	<b>Mower Deck</b>	DuraDeck™ Cutting System	DuraDeck™ Cutting System	DuraDeck™ Cutting System	DuraDeck™ Cutting System
	<b>Leading Edges</b>	Adjustable	Adjustable	Adjustable	Adjustable
	<b>Width</b>	36"	48"	52"	61"
	<b>Anti Scalp Rollers</b>	3	4	4	7
	<b>Cutting Height</b>	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"
	<b>Blade Tip Speed</b>	17,600 fpm @ 3,550 engine rpm	18,000 fpm @ 3,550 engine rpm	18,400 fpm @ 3,550 engine rpm	18,800 fpm @ 3,550 engine rpm
	<b>Discharge Chute</b>			Flexible molded polymer	
<b>FRAME</b>	<b>Form Welded</b>			Form welded with structural tubing	
	<b>Machine weight</b>	775 lb.	886 lb.	916 lb.	953 lb.
	<b>Machine Length</b>	64"	64"	64"	68"
<b>TRANSMISSION</b>	<b>Type</b>	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles
	<b>Displacement</b>	10 cc	12 cc	12 cc	12 cc
	<b>Oil Capacity</b>	4 qts.	4 qts.	4 qts.	4 qts.
	<b>Ground Speed</b>	9 mph	10.5 mph	10.5 mph	10.5 mph
	<b>Motion Control Levers</b>			Adjustable; Cut and Transport Speed Control	
<b>WHEELS</b>	<b>Drive Wheel Size</b>	20 x 8-10	23 x 8.5-12.0	23 x 10.5-12.0	23 x 10.5-12.0
	<b>Front Caster Size</b>	11 x 4.0-5	13 x 5.0-6	13 x 5.0-6	13 x 5.0-6
	<b>Caster Type</b>	Pneumatic	Pneumatic	Pneumatic	Pneumatic
<b>OPERATOR PLATFORM</b>	<b>Adjustment</b>	Flip up and latch	Flip up and latch	Flip up and latch	Flip up and latch
	<b>Rider pad</b>	Tethered, removable for service	Tethered, removable for service	Tethered, removable for service	Tethered, removable for service
	<b>Vibration Isolation</b>	Dampened	Dampened	Dampened	Dampened
<b>WARRANTY</b>					6-yr / 2000-hr Limited Warranty

**DURABILITY - QUALITY OF CUT - EASE OF OWNERSHIP**

HUNT DOWN YOUR NEAREST BOB-CAT® DEALER AT [BOBCATTURF.COM](http://BOBCATTURF.COM) | 866-469-1242

